



DEUTROPULS SW 2000

DEUTROPULS SW 1000

Transportable Current Flow Units

- for mobile operation
- for multiple use
- high, infinitely variable current
- current indicator

Technical data

	DEUTROPULS SW 1000 Alternating Current	DEUTROPULS SW 2000 Alternating Current	DEUTROPULS SW 3000 Alternating Current	DEUTROPULS SW 1000 G Direct Current*
Ordering no.	3454.001	3454.002	3454.003	3454.101
Inspection data				
Current, effective (A)	1000	2000	2890	1000 770*
Current control	infinitely variable	infinitely variable	infinitely variable	infinitely variable
Short circuit current (A)	4500	6000	> 6000	4500
Open-circuit voltage (V)	2,8	5	7,5	2,8
Relative duty cycle	30%	30%	30%	30%
Demagnetization	on request	on request	on request	
Operational data				
Mains supply	230 V 50/60 Hz	400 V 50/60 Hz	400 V 50/60 Hz	230 V 50/60 Hz
Power consumption (kW)	3	8,7	22	5,5
Dimensions				
L x W x H (mm)	395 x 275 x 255	470 x 335 x 265	470 x 355 x 305	510 x 320 x 275
Weight (kg)	25	41	59	32

*) half-wave rectified

Accessories

- Security foot switch
- Flexible high current cables (2,5 m and 5 m with 70 mm² or 120 mm²)
- Contact magnets (∅ 40 mm or ∅ 50 mm)

Find more accessories in our leaflet P 38 and our FLUXA detection media in P 90.

Please contact also our web-site: www.karldeutsch.de

